RULE BREAKER

Rule Breaker Tile 2B134

24 in x 24 in Carpet Tile



Product Type	Carpet Tile
Style	Rule Breaker Tile
Style #	2B134
Color	Cobalt
Color #	589
Collection	Rule Breaker
Fiber Type	Envirostrand Sd
Backing	Ultraset Matrix
Construction	Tufted
Size	24 in x 24 in
Surface Appearance	Level Loop
Dye Method	Solution Dyed
Installation Methods	Quarter Turn, Brick Ashlar, Vertical Ashlar
Pile Thickness	0.071
Total Thickness	0.172 "
Gauge	1/10 (39.37 rows per 10 cm)
Tufted Weight	14 oz/yd2 (475 g/m2)
Stitches Per Inch	10.2 (40.2 per 10cm)
Density	7098
Weight Density	99372
Flammability	ASTM E 648 Class I (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Soil Release Technology	Mohawk Protection Plus Soil
Recommended Adhesives	Enpress, M700 Plus, Flexlok + Tabs

Colorways



Cobalt

Color: 589



Praline

Color: 748



Hickory

Color: 869



Pewter

Color: 949



Nickel

Color: 959



Charcoal

Color: 979

Recommended Installation Methods



Quarter Turn



Brick Ashlar



Vertical Ashlar

Warranties

10 Year Stain Warranty

Ultraset Carpet Tile Warranty

Envirostrand Warranty

10 Year Limited Wear Warranty

10 Year Limited Static Protection Warranty

10 Year Limited Stain Resistance Warranty

10 Year Colorfastness to Light Warranty

10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Edge Ravel, Zippering, Delaminationand Dimensional Stability Warranty

Resources

Carpet Care

Carpet Tile Installation

Direct Glue-Down Installation