















This highly versatile floor offers delightful innovation with never-before-seen visuals in fresh, unique colorways. The Uniclic® locking system is milled into all four sides, producing a tight connection that installs quickly. A commercial grade wear layer and M-Force™ Enhanced Urethane finish ensure performance under heavy commercial traffic. The adhesive-free construction works over existing flooring and saves time and costs.

Urban Patina delivers a bit of mystery: its unusual mix of known species and organic inspired patterns provide hints of wood visuals without exactly replicating any specific type. Various textures ranging from linear to hardscraped are available in an easy-to-install 7" x 48" size.

- Commercial grade wear layer and
 M-Force[™] Enhanced Urethane finish
- Uniclic® locking system for fast, adhesive-free installation
- Four-sided locking system prevents plank separation ensuring a tight fit
- Installs on slabs with up to 95% RH and contains added antimicrobial
- More forgiving over uneven subfloors and is move-in ready
- Contains 30% recycled content
- FloorScore® certified

Color Effects

Solid, all loop textured tile available in 48 colors. Select colors also available as 12x36 plank. Install as a border, inset or accent tile.



EcoFlex[™] ICT carpet tile backing





PERFORMANCE

- Unsurpassed dimensional stability - no growing or shrinking
- Constructed with an ultra dense five layer cushion backing system
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Construction features superior tuft bind that is highly resistant to edge ravel
- Proven performance for over 15 years



BUDGET

 Superior construction offers reliability for the life of your installation



SUSTAINABILITY

- EcoFlex ICT contains 35% minimum pre consumer recycled content by total weight*
- Recyclable through Mohawk's ReCover program
- EcoFlex ICT may contribute to or comply with LEED® credits MR 4.0, IEQ 4.3 and Innovation credit for NSF 140
- CRI Green Label Plus certified
- Free of EPA phthalates of concern

- Certified at the Gold Level in accordance with NSF/ANSI 140 the Sustainability Assessment for Carpet
- NSF/ ANSI 140 Platinum level version available with a minimum of 10% post-consumer recycled content



SERVICE

• Engineered performance for an overall better after sales service experience

^{*} Recycled content claim third party verified by UL (Underwriters Laboratory)

EcoFlex[™] NXT AIR

carpet tile backing

EcoFlex[™] NXT AIR is a custom option for the Sense of Space collection and requires a minimum order of 500 sq. yds. and 10% overage.



Primary Backing

EcoFlex™ NXT AIR offers substantial sound reduction and enhanced comfort under foot. It also incorporates an average of 50% recycled content (pre- and post-consumer) by total product weight.



PERFORMANCE

- Provides permanent tile dimensional stability
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Noise Reduction Coefficient is 0.30 - carpet tiles should reduce sound by 30%
- Impact Insulation Class 70 our product is more than 2x better in reducing sound transmission than hard surfaces and 40% better than standard carpet
- Construction features superior tuft bind that is highly resistant to edge ravel

- Provides additional thermal resistance (R-Value) reducing HVAC workload and cost
- Increased load deflection reduces physical stress and provides comfort under foot - the perfect solution for today's sit/stand work environments and high traffic areas
- Reduces the risk of injuries in the event of a slip or fall - a common concern in healthcare and assisted living facilities



SUSTAINABILITY

- · Contains no plasticizers
- PET Cushion layer of EcoFlex NXT AIR is 95% post consumer recycled content.
- Finished product contains a total of 38% pre consumer and 12%

- post consumer recycled content or 50% total recycled content by total product weight
- Certified NSF/ ANSI 140 Platinum with a minimum of 10% post consumer recycled content
- EcoFlex NXT AIR may contribute to or comply with LEED® credits MR 4.0
- CRI Green Label Plus certified
- Mohawk Group is leading the entire manufacturing sector in the Living Building Challenge™ Declare program



SERVICE

- Engineered performance for an overall better after sales service experience
- Contact your sales representative for more information

^{*} Recycled content claim third party verified by UL (Underwriters Laboratory)

Brand	Durkan
Style Name / Number	Classic Form / MD011
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Dye Method	Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Sentry Plus Stain Protection
Soil Release Technology	Sentry Soil Protection
Backing Material	EcoFlex ICT
Indoor Air Quality	Green Label Plus Certified # 1098
NSF 140	Gold
Size	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Brick Ashlar /
	Vertical Ashlar / Monolithic /
	Multi Directional
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC - 134 Under 3.5 KV
Warranties: Lifetime Limited (Carpet Tile Warranty, Lifetime Limited
Colorfastness to Light, 10 Yea	r Limited Colorfastness to

Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static

	Brand	Durkan Modern Functional / MD012 Tufted Textured Patterned Loop 1/12" (47.00 rows per 10 cm) Solution Dyed Colorstrand® SD Nylon Sentry Plus Stain Protection Sentry Soil Protection EcoFlex ICT Green Label Plus Certified # 1098 Gold 24" x 24" (.6096 m x .6096 m) Quarter Turn / Brick Ashlar / Vertical Ashlar / Monolithic /
	• • • • • • • • • • • • • • • • • • • •	•
ı	•	
ı	· ·	Gold
ı	Size	24" x 24" (.6096 m x .6096 m)
ı	Installation Method	Quarter Turn / Brick Ashlar /
ı		Vertical Ashlar / Monolithic /
		Multi Directional
ı		ASTM E 648 Class 1 (Glue Down)
	Smoke Density	
	Static Propensity	
ı		Carpet Tile Warranty, Lifetime Limited
	Colorfastness to Light, 10 Yea	
	Atmospheric Contaminants, 1	0 Year Stain Warranty, Lifetime Stati

24BY24

]	Brand	Durkan
ı	Style Name / Number	Elegantly Smart / MD013
1	Construction	Tufted
۱	Surface Appearance	Textured Patterned Loop
1	Gauge	1/12" (47.00 rows per 10 cm)
ı	Dye Method	Solution Dyed
ı	Fiber Type	Colorstrand® SD Nylon
ı	Stain Release Technology	Sentry Plus Stain Protection
ı	Soil Release Technology	Sentry Soil Protection
ı	Backing Material	EcoFlex ICT
ı	Indoor Air Quality	Green Label Plus Certified # 1098
ı	NSF 140	Gold
ı	Size	24" x 24" (.6096 m x .6096 m)
ı	Installation Method	Quarter Turn / Brick Ashlar /
ı		Vertical Ashlar / Monolithic /
ı		Multi Directional
ı	Flammability	ASTM E 648 Class 1 (Glue Down)
ı	Smoke Density	ASTM E 662 Less than 450
ı	Static Propensity	AATCC - 134 Under 3.5 KV
ı	Warranties: Lifetime Limited (Carpet Tile Warranty, Lifetime Limited
ı	Colorfastness to Light, 10 Year	r Limited Colorfastness to
ı	Atmospheric Contaminants, 1	0 Year Stain Warranty, Lifetime Static

	Brand	Durkan
_	Style Name / Number	Stately Stylish / MD014
24BY24	Construction	Tufted
B	Surface Appearance	Textured Patterned Loop
24	Gauge	1/12" (47.00 rows per 10 cm)
	Dye Method	Solution Dyed
	Fiber Type	Colorstrand® SD Nylon
	Stain Release Technology	Sentry Plus Stain Protection
	Soil Release Technology	Sentry Soil Protection
	Backing Material	EcoFlex ICT
	Indoor Air Quality	Green Label Plus Certified # 1098
	NSF 140	Gold
	Size	24" x 24" (.6096 m x .6096 m)
	Installation Method	Quarter Turn / Brick Ashlar /
		Vertical Ashlar / Monolithic /
		Multi Directional
	Flammability	
	Smoke Density	ASTM E 662 Less than 450
	Static Propensity	AATCC - 134 Under 3.5 KV
	Warranties: Lifetime Limited (Carpet Tile Warranty, Lifetime Limite
	Colorfastness to Light, 10 Yea	r Limited Colorfastness to
	4	0.1/ 0. 1 14/ . 11/ .1 0

Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static

Installation Instructions:

Monolithic	Quarter Turn	Brick Ashlar	Vert. Ashlar	Multi-Directional
† † † † † † † † †	↑ → ↑ → ↑ → ↑ → ↑	† † † † † †	1 1 1 1 1 1	↑ ↓ ← → ↑ → ← → ↓



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Moving Along Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit durkan.com











I	Brand	Durkan
ı	Style Name / Number	Defining Vision / MD015
ı	Construction	Tufted
ı	Surface Appearance	Textured Patterned Loop
ı	Gauge	1/12" (47.00 rows per 10 cm)
ı	Dye Method	Solution Dyed
ı	Fiber Type	Colorstrand® SD Nylon
ı	Stain Release Technology	Sentry Plus Stain Protection
ı	Soil Release Technology	Sentry Soil Protection
ı	Backing Material	EcoFlex ICT
ı	Indoor Air Quality	Green Label Plus Certified # 1098
ı	NSF 140	Gold
ı	Size	24" x 24" (.6096 m x .6096 m)
ı	Installation Method	Quarter Turn / Brick Ashlar /
ı		Vertical Ashlar / Monolithic /
ı		Multi Directional
ı	Flammability	ASTM E 648 Class 1 (Glue Down)
ı	Smoke Density	
ı	Static Propensity	
	' '	Carpet Tile Warranty, Lifetime Limited
	Colorfastness to Light, 10 Yea	'
ı	to Light, to roo	

Atmospheric Contaminants, 10 Year Stain Warranty, Lifetime Static

24BY24

Brand	Durkan
Style Name / Number	Sleek Find / MD016
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Dye Method	Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Sentry Plus Stain Protection
Soil Release Technology	Sentry Soil Protection
Backing Material	EcoFlex ICT
Indoor Air Quality	Green Label Plus Certified # 1098
NSF 140	Gold
Size	24" x 24" (.6096 m x .6096 m)
Installation Method	Quarter Turn / Brick Ashlar /
	Vertical Ashlar / Monolithic /
	Multi Directional
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC - 134 Under 3.5 KV
Warranties: Lifetime Limited (Carpet Tile Warranty, Lifetime Limite
Colorfastness to Light, 10 Yea	r Limited Colorfastness to
Atmospheric Contaminants, 1	0 Year Stain Warranty, Lifetime Stati

24BY24

For Color Effects and LVT spec information, visit our website at durkan.com.

Installation Instructions:

Monolithic	Quarter Turn	Brick Ashlar	Vert. Ashlar	Multi-Directiona
† † † † † † † † †	↑ → ↑ → ↑ → ↑ → ↑	† † † † † †	† † † † † †	↑ ↓ ← → ↑ → ← → ↓



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Moving Along Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit durkan.com









