

Shared Strides

Overview

Factoria	Description
Feature	Description
Collection	Link Step
Style	Shared Strides (C2100)
Product Type	LVT
Size	6 in x 48 in
Construction	Light Commercial LVT
Gauge	2 mm
Total Thickness	2 mm
Wear Layer	12 mil (0.3 mm)
Finish	Enhance Urethane
Edge Profile	Squared Edge
Installation	Glue Down
Installation Method	Brick Ashlar, Herringbone, Random
Recommended Adhesive	M95.0, MS160 or M700 Plus



Recommended Installation Methods







Brick Ashlar

Herringbone

Random

Colorways



Connecting Cool

945 Color code: Style number: C2100



Affinity Suede

Color code: 838 Style number: C2100



Radiating Shadow

Color code: 942 Style number: C2100



Unified Tone

Color code: 842 Style number: C2100



Elevated Silver

818 Color code: Style number: C2100



Haute Confluence

Color code: 848 Style number: C2100



















Colorways



Embracing Ember

Color code: Style number: C2100

Testing

Feature	Description
Classification	(ASTM F1700) Type B - Embossed
Squareness	(ASTM F 2421) ±0.10" max
Size and Tolerance	(ASTM F2421) Passes
Thickness	(ASTM F386) ±0.005"
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) 1000 psi
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) <450
Wear Layer Thickness	12 mil (0.3 mm)
Lightfastness	(ASTM F1515) Passes
Light Reflectancy	36

Sustainability

Feature	Description
Embodied Carbon	11.9 kg CO2e/sq m2
Beyond Carbon Neutral	-0.279
Country of Origin	Vietnam

Packaging

Feature	Description
Pieces per Carton	27
Weight per Piece (lbs)	1.4
Cartons Per Pallet	60
Square Feet per Carton	54
Weight per Carton (lbs)	37.5

















Warranties

Limited 10 Year Light Commercial Warranty, 25 Year Residential Warranty







