


Shenandoah Valley

Overview

Feature	Description
Collection	Residence
Style	Shenandoah Valley (C2109)
Product Type	LVT
Size	7.13 in x 48.03 in
Construction	Rigid LVT with attached pad
Total Thickness	4.5 mm
Wear Layer	12 mil
Finish	Enhanced Urethane
Edge Profile	Micro Bevel
Installation	Click
Installation Method	Brick Ashlar, Random



Recommended Installation Methods



Brick Ashlar



Random

Colorways



Poplar

Color code: 235
Style number: C2109



Oak Hill

Color code: 817
Style number: C2109



Monticello

Color code: 821
Style number: C2109



Ash Lawn

Color code: 838
Style number: C2109



Mount Vernon

Color code: 929
Style number: C2109



Berkeley

Color code: 207
Style number: C2109

Colorways



Sherwood

Color code: 212
Style number: C2109



Montpelier

Color code: 219
Style number: C2109

Testing

Feature	Description
Squareness	(ASTM F 2421) ± 0.10 " max
Size and Tolerance	(ASTM F2421) Passes
Thickness	(ASTM F386) ± 0.005 "
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) 1000 psi
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) <450
Wear Layer Thickness	12 mil
Lightfastness	(ASTM F1515) Passes

Sustainability

Feature	Description
Embodied Carbon	8.24 kg CO2e/sq m2

Packaging

Feature	Description
Pieces per Carton	14
Weight per Piece (lbs)	3.5
Cartons Per Pallet	55
Square Feet per Carton	33.64
Weight per Carton (lbs)	48.8

Warranties

10 Year Light Commercial