

**HOT AND HEAVY II**

**Chromascope 5.0 C2114**

18 in x 36 in LVT




<b>Collection</b>	Hot and Heavy II
<b>Style</b>	Chromascope 5.0 (C2114)
<b>Product Type</b>	LVT
<b>Size</b>	18 in x 36 in
<b>Construction</b>	Commercial LVT
<b>Gauge</b>	5 mm
<b>Total Thickness</b>	5 mm
<b>Wear Layer</b>	20 mil (0.5 mm)
<b>Finish</b>	M-Force™ Ultra
<b>Surface Profile</b>	Overall
<b>Edge Profile</b>	Squared
<b>Installation</b>	Loose Lay
<b>Recommended Adhesive</b>	M95.0, M99, MS160, M700 Plus, or Total Bond Adhesive

**Recommended Installation Methods**



Brick Ashlar



Herringbone



Monolithic



Random

**Colorways**



Buff Ivory  
Color: 120



Tan Essence  
Color: 230




Peach Bliss  
Color: 237



Melon Harmony  
Color: 248



Cozy Linen  
Color: 250



Warm Haven  
Color: 270



**Muted Maroon**  
Color: 344



**Radiant Gold**  
Color: 360



**Crimson Glow**  
Color: 374




**Orange Embrace**  
Color: 440




**Purple Dream**  
Color: 475




**Violet Cascade**  
Color: 540



**Red Flame**  
Color: 550



**Regal Blue**  
Color: 555



**Soft Sky**  
Color: 620




**Serene Navy**  
Color: 650




**Tranquil Teal**  
Color: 672



**Celestial Forest**  
Color: 676




**Fresh Sprout**  
Color: 760



**Restorative Green**  
Color: 790




**Gentle Haze**  
Color: 910



**Balanced Charcoal**  
Color: 940



**Whispering Grey**  
Color: 960



**Grounded Black**  
Color: 980

## Testing

<b>Classification</b>	(ASTM F1700) Class III, Type B - Embossed
<b>Squareness</b>	(ASTM F2421) Passes
<b>Size and Tolerance</b>	(ASTM F2421) Passes
<b>Thickness</b>	(ASTM F386) Passes
<b>Flexibility</b>	(ASTM F137) Passes
<b>Dimensional Stability</b>	(ASTM F2199) Passes
<b>Static Load Limit</b>	(ASTM F970) 1000 psi
<b>Lightfastness</b>	(ASTM F1515) Passes
<b>Residual Indentation</b>	(ASTM F1914) Passes
<b>Resistance to Chemicals</b>	(ASTM F925) Passes
<b>Resistance to Light</b>	(ASTM F1515) Passes
<b>Resistance to Heat</b>	(ASTM F1514) Passes
<b>Radiant Flux</b>	(ASTM E648) Class 1
<b>Smoke Density</b>	(ASTM E662) = 450
<b>Slip Resistance</b>	NFSI B101.1/B101.3 Slip Resistant Certified
<b>Wear Layer Thickness</b>	20 mil (0.5 mm)
<b>Light Reflectancy</b>	41

## Sustainability

---

<b>Embodied Carbon</b>	6.43 kg CO <sub>2</sub> e/m <sup>2</sup>
<b>EPD</b>	Hot and Heavy II 5.0 mm EPD

## Packaging

---

<b>Square Feet Per Carton</b>	27
<b>Pieces Per Carton</b>	6
<b>Cartons Per Pallet</b>	46