

HOT AND HEAVY II

Bolder 3.0 PVC Free C2130

18 in x 36 in Resilient Tile




Collection	Hot and Heavy II
Style	Bolder 3.0 PVC Free (C2130)
Product Type	Resilient Tile
Size	18 in x 36 in
Construction	PVC Free
Gauge	3 mm
Total Thickness	3 mm
Wear Layer	20 mil (0.5 mm)
Finish	M-Force™ Ultra
Surface Profile	Embossed
Edge Profile	Squared
Installation	Glue Down
Recommended Adhesive	FlexPress or Total Bond Adhesive

Recommended Installation Methods



Brick Ashlar



Herringbone

Colorways



Inferno
Color: 269



Bronze
Color: 832



Dune
Color: 838



Flint
Color: 848



Aura
Color: 859



Slate
Color: 925



Celestial
Color: 929



Silk
Color: 938



Lava
Color: 949



Shine
Color: 959



Obsidian
Color: 969

Testing

Classification	(ASTM F1700) Type B - Embossed
Squareness	(ASTM F 2421) ±0.10" max
Size and Tolerance	(ASTM F2421) Passes
Thickness	(ASTM F386) ±0.005"
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) Passes, modified at 2100 PSI
Lightfastness	(ASTM F1515) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) = 450
Slip Resistance	NFSI B101.1/B101.3 Slip Resistant Certified
Wear Layer Thickness	20 mil (0.5 mm)
Light Reflectancy	28

Sustainability

HPD	Hot and Heavy II PVC-Free 3.0 mm HPD
Material Health	Red List Free

Packaging

Square Feet Per Carton	54
Pieces Per Carton	12
Cartons Per Pallet	40