

ASSEMBLED WOODS

Planked C2132

6 in x 36 in LVT




Collection	Assembled Woods
Style	Planked (C2132)
Product Type	LVT
Size	6 in x 36 in
Construction	Commercial LVT
Total Thickness	5.0 mm
Wear Layer	20 mil (0.5mm)
Finish	M-Force™ Ultra
Surface Profile	Overall
Edge Profile	Squared
Installation	Loose Lay
Recommended Adhesive	M95.0, M99, MS160, M700 Plus, or Total Bond Adhesive

Recommended Installation Methods



Brick Ashlar



Herringbone



Monolithic



Random


Colorways




Goldenrod Oak
Color: 128




Butterscotch Oak
Color: 148



Wheat Oak
Color: 829



Harvest Oak
Color: 832



Safari Oak
Color: 843



Autumn Oak
Color: 849



Clay Oak
Color: 852



Tobacco Oak
Color: 863



Windy Oak
Color: 931



Umber Oak
Color: 951

Testing

Classification	(ASTM F1700) Type B - Embossed
Squareness	(ASTM F 2421) ±0.10" max
Size and Tolerance	(ASTM F2421) Passes
Thickness	(ASTM F386) ±0.005"
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) 1000 psi
Lightfastness	(ASTM F1515) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) <450
Wear Layer Thickness	20 mil (0.5mm)
Light Reflectancy	36

Sustainability

Embodied Carbon	6.43 kg CO2e/m2
Beyond Carbon Neutral	-0.58 kg CO2e/m2

Packaging

Square Feet Per Carton	17.98
Pieces Per Carton	12
Cartons Per Pallet	72

Warranties

Limited 20 Year M-Force Ultra Commercial Warranty