

VIVID STEP

Vivid Step Wood CR705

6 in x 48 in LVT



Collection	Vivid Step
Style	Vivid Step Wood (CR705)
Product Type	LVT
Size	6 in x 48 in
Construction	Light Commercial LVT
Gauge	2 mm
Total Thickness	2 mm
Wear Layer	12 mil (0.3 mm)
Finish	Enhanced Urethane
Edge Profile	Beveled
Installation	Glue Down
Recommended Adhesive	M95.0, M99, MS160, M700 Plus, or Total Bond Adhesive


Recommended Installation Methods



Brick Ashlar



Half Lap



Herringbone



Random

Colorways



Shimmering Sand

Color: W128




Grounded Hatch

Color: W132




Golden Pine

Color: W236



Candied Pecan

Color: W719



Vintage Oak

Color: W723



Beary Brown


Color: W746



Sable Birch
Color: W754



Roasted Kaffee
Color: W863



Java Hut
Color: W898



Turkish Blend
Color: W959



Deep Gris
Color: W979



Perfect Portobello
Color: W989

Testing

Classification	(ASTM F1700) Class III, Type B, Embossed
Squareness	(ASTM F2421) ±0.10 in
Size and Tolerance	(ASTM F2421) ±0.016 in
Thickness	(ASTM F386) ± .005 in
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) 1000 psi
Lightfastness	(ASTM F1515) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) = 450
Wear Layer Thickness	12 mil (0.3 mm)

Sustainability

Embodied Carbon	11.9 kg CO2e/m2
Carbon Handprint	-12.5 kg CO2e/m2
Beyond Carbon Neutral	-0.595 kg CO2e/m2
EPD	Vinyl Tile EPD
Material Health	Free of Orthophthalates and Heavy Metals
LEED	Calculate LEED on Ecomedes
Mindful Materials	Participates in Mindful Materials Library
MindClick Rating	Achiever
Country of Origin	Korea

Packaging

Square Feet Per Carton	54
Pieces Per Carton	27
Cartons Per Pallet	60

Warranties

[Limited 10 Year Light Commercial Warranty](#)