

# Transfiguration 4.5

## Overview

| Feature              | Description  |
|----------------------|--|
| Collection           | Taking Root  |
| Style                | Transfiguration 4.5 (C2088)                          |
| Product Type         | LVT  |
| Size                 | 18" X 36"  |
| Construction         | Commercial LVT                                       |
| Gauge                | 4.5 mm   |
| Total Thickness      | 4.5 mm   |
| Wear Layer           | 20 mil (0.5 mm)                                      |
| Finish               | M-Force™ Ultra                                       |
| Surface Profile      | Embossed   |
| Edge Profile         | Micro-Beveled  |
| Installation         | Glue Down  |
| Installation Method  | Brick Ashlar, Half Lap, Herringbone, Random          |
| Recommended Adhesive | M95.0, M99, MS160, M700 Plus, or Total Bond Adhesive |




## Recommended Installation Methods



Brick Ashlar



Half Lap



Herringbone



Random

## Colorways



### Shift

Color code: 929  
Style number: C2088



### Modify

Color code: 828  
Style number: C2088



### Variation

Color code: 859  
Style number: C2088



### Alter

Color code: 969  
Style number: C2088



### Reshape

Color code: 825  
Style number: C2088

## Testing

| Feature                 | Description                              |
|-------------------------|--|
| Classification          | (ASTM F1700) Class III, Type B, Embossed |
| Squareness              | (ASTM F2421) ±0.10 in                    |
| Size and Tolerance      | (ASTM F2421) ±0.016 in                   |
| Thickness               | (ASTM F386) ± .005 in                    |
| Flexibility             | (ASTM F137) Passes                       |
| Dimensional Stability   | (ASTM F2199) Passes                      |
| Static Load Limit       | (ASTM F970) 1000 psi                     |
| Residual Indentation    | (ASTM F1914) Passes                      |
| Resistance to Chemicals | (ASTM F925) Passes                       |
| Resistance to Light     | (ASTM F1515) Passes                      |
| Resistance to Heat      | (ASTM F1514) Passes                      |
| Radiant Flux            | (ASTM E648) Class 1                      |
| Smoke Density           | (ASTM E662) □ 450                        |
| Wear Layer Thickness    | 20 mil (0.5 mm)                          |
| Lightfastness           | (ASTM F1515) Passes                      |

## Sustainability

| Feature                       | Description                              |
|-------------------------------|--|
| Embodied Carbon               | 6.65 kg CO2e/sq m2                       |
| Carbon Handprint              | -6.98 kg CO2e/sq m2                      |
| Beyond Carbon Neutral         | -0.333                                   |
| Pre-Consumer Recycled Content | 100%                                     |
| EPD                           | Flex 4.5 LVT EPD                         |
| Material Health               | Free of Orthophthalates and Heavy Metals |
| Specify for a Cure            | Eligible                                 |
| Mindful Materials             | Participates                             |
| MindClick Rating              | Achiever                                 |
| Country of Origin             | USA                                      |

## Packaging

| Feature                | Description |
|------------------------|-------------|
| Pieces per Carton      | 7           |
| Weight per Piece       | 7.29        |
| Cartons Per Pallet     | 30          |
| Square Feet per Carton | 31.5        |
| Weight per Carton      | 51.03       |

# Warranties

---

Limited 20 Year M-Force Ultra Commercial Warranty