

## Zone Lines Rigid

### Overview

Feature	Description
Collection	Taking Root
Style	Zone Lines Rigid (C2086)
Product Type	LVT
Size	7.46" X 47.80"
Construction	Rigid LVT
Gauge	6 mm
Total Thickness	6 mm
Wear Layer	20 mil (0.5 mm)
Finish	M-Force™ Ultra
Surface Profile	Embossed
Edge Profile	Micro-Beveled
Installation	Click
Installation Method	Brick Ashlar, Half Lap, Random
Recommended Adhesive	None Required
Core Type	Solid Polymer Core (SPC)



### Recommended Installation Methods



Brick Ashlar



Half Lap



Random

### Colorways



#### Water

Color code: 569  
Style number: C2086



#### Time

Color code: 834  
Style number: C2086



#### Dotting

Color code: 849  
Style number: C2086



#### Oxygen

Color code: 945  
Style number: C2086



#### Temperature

Color code: 989  
Style number: C2086

## Testing

Feature	Description
Classification	(ASTM F1700) Class III, Type B, Embossed
Squareness	(ASTM F2421) ±0.10 in
Size and Tolerance	(ASTM F2421) ±0.016 in
Thickness	(ASTM F386) ± .005 in
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) 1000 psi
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) ≤ 450
Wear Layer Thickness	20 mil (0.5 mm)
Lightfastness	(ASTM F1515) Passes

## Sustainability

Feature	Description
Embodied Carbon	11.9 kg CO2e/sq m2
Carbon Handprint	-12.5 kg CO2e/sq m2
Beyond Carbon Neutral	-0.595
EPD	EPD Vinyl Tile
Material Health	Free of Orthophthalates and Heavy Metals
LEED	<a href="#">Calculate LEED on Ecomedes</a>
Specify for a Cure	Eligible
Mindful Materials	Participates
MindClick Rating	Achiever
Country of Origin	Mexico

## Packaging

Feature	Description
Pieces per Carton	9
Weight per Piece	2.3
Cartons Per Pallet	50
Square Feet per Carton	22.23
Weight per Carton	20.7

# Warranties

---

Limited 20 Year M-Force Ultra Commercial Warranty