Mohawk Group

VARIANT FORM


Diffuse BT425

12 in x 36 in Carpet Tile



Collection	Variant Form
Style	Diffuse (BT425)
Product Type	Carpet Tile
Size	12 in x 36 in
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Fiber	ColorStrand® Nylon
Dye Method	Solution Dyed
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	Ecoflex Matrix
Tufted Pile Weight	16 oz/yd2 (542 g/m2)
Pile Height	0.091
Gauge	1/12 (47.00 rows per 10 cm)
Stitches per Inch	12.3 (48.4 per 10cm)
Pile Thickness	0.091
Density	6329
Installation	FlexLok, Glue Down
Recommended Adhesive	Enpress, M700 Plus, FlexLok+ Tabs, Total Bond

Recommended Installation Methods




Basket Weave



Brick Ashlar




Half Lap




Herringbone



Monolithic



Monolithic Stepping



Plank Half Lap



Random

Mohawk Group

Colorways




Concrete
Color: 358




Aggregate
Color: 751



Fuse
Color: 859



Lumen
Color: 955



Masonry
Color: 983



Asphalt
Color: 999

Testing

TARR Rating	Heavy
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

Sustainability

Embodied Carbon	7.19 kg CO2e/m2
Carbon Handprint	-7.55 kg CO2e/m2
Beyond Carbon Neutral	-0.36 kg CO2e/m2
Total Recycled Content	41.33%
Pre-Consumer Recycled Content	41.33%
EPD	EcoFlex Matrix EPD
HPD	EcoFlex Matrix HPD
Material Health	Declare Red List Free
NSF 140	EcoFlex Matrix - NSF 140 Gold
LEED	Calculate LEED on Ecomedes
Indoor Air Quality	GLP 1171
Specify for a Cure	Eligible
Mindful Materials	Participates
MindClick Rating	Achiever
End of Life	ReCover
Country Of Origin	USA

Packaging

Square Yards Per Carton	8.00
Pieces Per Carton	24
Cartons Per Pallet	44

Warranties

Lifetime Limited Carpet Tile Warranty

Lifetime Limited Colorfastness to Light

10 Year Limited Colorfastness to Atmospheric Contaminants

10 Year Limited Stain Warranty