Mohawk Group

ART INTERVENTION


Draft Point BT427

24 in x 24 in Carpet Tile




Collection	Art Intervention
Style	Draft Point (BT427)
Product Type	Carpet Tile
Size	24 in x 24 in
Construction	Tufted
Surface Appearance	Level Loop
Fiber	ColorStrand® Nylon
Dye Method	Solution Dyed
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	Ecoflex Matrix
Tufted Pile Weight	16 oz/yd2 (542 g/m2)
Pile Height	0.000
Gauge	1/10 (39.37 rows per 10 cm)
Stitches per Inch	12.2 (48 per 10cm)
Pile Thickness	0.000
Total Thickness	0.196 "
Density	5333
Installation	FlexLok, Glue Down
Recommended Adhesive	Enpress, M700 Plus, FlexLok+ Tabs, Total Bond


Recommended Installation Methods




Brick Ashlar




Monolithic



Multi Directional



Quarter Turn




Vertical Ashlar

Mohawk Group


Colorways




Sand
Color: 847



Pewter
Color: 959



Iron
Color: 979



Jet
Color: 989

Testing

TARR Rating	Heavy
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

Sustainability

Embodied Carbon	7.19 kg CO2e/m2
Carbon Handprint	-7.55 kg CO2e/m2
Beyond Carbon Neutral	-0.36 kg CO2e/m2
Total Recycled Content	41.33%
Pre-Consumer Recycled Content	41.33%
EPD	EcoFlex Matrix EPD
HPD	EcoFlex Matrix HPD
Material Health	Declare Red List Free
NSF 140	EcoFlex Matrix - NSF 140 Gold
LEED	Calculate LEED on Ecomedes
Mindful Materials	Participates
MindClick Rating	Achiever
End of Life	ReCover
Country Of Origin	USA

Packaging

Square Yards Per Carton	10.67
Pieces Per Carton	24
Cartons Per Pallet	22

Warranties

Lifetime Limited Carpet Tile Warranty

Lifetime Limited Colorfastness to Light

10 Year Limited Colorfastness to Atmospheric Contaminants

10 Year Limited Stain Warranty