

Interplay Stripe

Overview

Feature	Description
Collection	Learn and Live
Style	Interplay Stripe (GL416)
Product Type	Broadloom
Size	12 ft
Pattern Repeat	18"W X 35.5"L
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Fiber	Duracolor® Tricor Premium Nylon
Dye Method	Solution Dyed
Stain Release Technology	Permanent, Built into the Fiber
Soil Release Technology	EcoSentry Soil Protection
Backing	Unibond Plus/Weldlok
Pile Weight	28 oz/yd2 (949 g/m2)
Gauge	1/12 (47.00 rows per 10 cm)
Stitches per Inch	8.17 (32.2 per 10cm)
Pile Thickness	0.107
Density	9420
Installation	Glue Down, Double Stick, Tackless
Installation Method	Side Match
Recommended Adhesive	NuBroadlok Premium Plus, NuBroadlok VRT, NuBroadlok Edge Sealer, NuBroadlok Moisture Proof Latex Seam Sealer



Colorways

 Yellow Jacket Color code: 951 Style number: GL416	 Summer Nights Color code: 965 Style number: GL416	 Baked Clay Color code: 968 Style number: GL416
 Heartfelt Color code: 989 Style number: GL416		

Testing

Feature	Description
TARR Rating	Severe
GSA Stain Release	Pass
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

Sustainability

Feature	Description
Embodied Carbon	14.9 kg CO2e/sq m2
Carbon Handprint	-15.645 kg CO2e/sq m2
Beyond Carbon Neutral	-0.745
Total Recycled Content	31%
EPD	Unibond Plus EPD
HPD	Unibond Plus HPD
Material Health	Declare Red List Free
NSF 140	Unibond Plus - NSF 140 Gold
LEED	Calculate LEED on Ecomedes
Indoor Air Quality	GLP 3802
Mindful Materials	Participates
MindClick Rating	Leader
End of Life	Eligible
Country Of Origin	USA

Warranties

Lifetime Limited Unibond® Plus Warranty, Lifetime Duracolor Stain Warranty, Lifetime Static