

Chromatic Cadence

Overview

Feature	Description
Collection	Chromatic Cadence
Style	Chromatic Cadence (BT596)
Product Type	Carpet Tile
Size	24" X 24"
Construction	PDI
Surface Appearance	Textured Patterned Cut & Loop
Fiber	ColorStrand® Nylon
Dye Method	Precision Dyed Injection
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	Ecoflex Air
Pile Weight	26.00 oz/yd ² (882 g/m ²)
Gauge	1/12 (47.00 rows per 10cm)
Stitches per Inch	10.5 (41.34 per 10cm)
Total Thickness	0.359" (9.12 mm)
Installation	FlexLok
Recommended Adhesive	Enpress, M700 Plus, FlexLok+ Tabs, Total Bond
Protective Finishes	Chloraguard®



Colorways



Magenta Haze

Color code: 354
Style number: BT596



Purple Rain

Color code: 454
Style number: BT596



Summertime

Color code: 142
Style number: BT596



Sunny Side

Color code: 151
Style number: BT596



Magic Touch

Color code: 252
Style number: BT596



Spell On You

Color code: 353
Style number: BT596



Love Tko

Color code: 373
Style number: BT596



La Vie En Rose

Color code: 424
Style number: BT596



Right Place

Color code: 444
Style number: BT596

Colorways



Blue Skies

Color code: 535
Style number: BT596



Blueberry Hill

Color code: 555
Style number: BT596



Just For A Thrill

Color code: 566
Style number: BT596



Its A Blue World

Color code: 575
Style number: BT596



Kind Of Blue

Color code: 584
Style number: BT596



Kozmic Blues

Color code: 595
Style number: BT596



Willow Weep

Color code: 636
Style number: BT596



Stardust

Color code: 651
Style number: BT596



Being Green

Color code: 656
Style number: BT596



Lush Life

Color code: 676
Style number: BT596



Fine And Mellow

Color code: 737
Style number: BT596



Stormy Monday

Color code: 778
Style number: BT596



Sweet Georgia Brown

Color code: 878
Style number: BT596



Smokestack Lightning

Color code: 927
Style number: BT596



Stone Crazy

Color code: 958
Style number: BT596



Round Midnight

Color code: 989
Style number: BT596

Testing

Feature	Description
TARR Rating	Severe
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

Sustainability

Feature	Description
Embodied Carbon	10.3 kg CO2e/sq m2
Carbon Handprint	-10.82 kg CO2e/sq m2
Beyond Carbon Neutral	-0.56
Pre-Consumer Recycled Content	44%
Post-Consumer Recycled Content	10%
EPD	0
HPD	EcoFlex AIR HPD
Material Health	Declare Red List Free
NSF 140	EcoFlex AIR - NSF 140 Gold
LEED	Calculate LEED on Ecomedes
Indoor Air Quality	GLP 1256
Specify for a Cure	Eligible
Mindful Materials	Participates
MindClick Rating	0
Country Of Origin	USA

Packaging

Feature	Description
Square Yards Per Carton	6.22
Cartons Per Pallet	20
Weight Per Carton	47.46

Warranties

Lifetime Limited Carpet Tile Warranty, Lifetime Static