

### **Draft Point**

### Overview

Feature	Description
Collection	Art Intervention
Style	Draft Point (BT427)
Product Type	Carpet Tile
Size	24" X 24"
Construction	Tufted
Surface Appearance	Level Patterned Loop
Fiber	ColorStrand® Nylon
Dye Method	Solution Dyed
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	EcoFlex Matrix
Pile Weight	16.00 oz/yd2 (543 g/m2)
Gauge	1/10 (39.37 rows per 10 cm)
Stitches per Inch	12.2 (48.03 per 10cm)
Pile Thickness	.108" (2.74 mm)
Total Thickness	0.368" (9.35 mm)
Density	5333
Installation	FlexLok
Installation Method	Quarter Turn, Monolithic, Brick Ashlar,
	Vertical Ashlar, Multi-Directional
Recommended Adhesive	Enpress, M700 Plus, FlexLok+ Tabs, Total
	Bond



### **Recommended Installation Methods**












Quarter Turn

Monolithic

Brick Ashlar

Vertical Ashlar

Multi-Directional













# Mohawk Group

# Colorways



#### Sand

Color code: 847 BT427 Style number:



#### **Pewter**

Color code: 959 Style number: BT427



#### Iron

Color code: 979 BT427 Style number:



#### Jet

Color code: 989 Style number: BT427

## **Testing**

Feature	Description
TARR Rating	Heavy
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

## Sustainability

Feature	Description
Embodied Carbon	7.19 kg CO2e/sq m2
Carbon Handprint	-7.55 kg CO2e/sq m2
Beyond Carbon Neutral	-0.36
Total Recycled Content	45%
Pre-Consumer Recycled Content	45%
EPD	EcoFlex Matrix EPD
HPD	EcoFlex Matrix HPD
Material Health	Declare Red List Free
NSF 140	EcoFlex Matrix - NSF 140 Gold
LEED	Calculate LEED on Ecomedes
Indoor Air Quality	GLP 1171
Mindful Materials	Participates
MindClick Rating	Achiever
End of Life	ReCover
Country Of Origin	USA

## **Packaging**

Feature	Description
Square Yards Per Carton	10.67
Cartons Per Pallet	22
Weight Per Carton	37.92















# Ⅲ Mohawk Group

### Warranties

Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static







