

# London Thyme

## Overview

Feature	Description
Collection	Abbey Grove
Style	London Thyme (BC590)
Product Type	Broadloom
Size	12Ft 00In
Pattern Repeat	36.0"W X 44.0"L
Construction	Tufted
Surface Appearance	Patterned Tip Shear
Fiber	ColorStrand® Nylon
Dye Method	Solution Dyed
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	Weldlok
Pile Weight	32.00 oz/yd2 (1085 g/m2)
Gauge	1/12 (47.00 rows per 10 cm)
Stitches per Inch	9 (35.43 per 10cm)
Pile Thickness	0.343" (8.73 mm)
Total Thickness	0.313" (7.95 mm)
Installation	Glue Down, Double Stick, Tackless
Installation Method	Side Match
Recommended Adhesive	NuBroadlok Premium Plus, NuBroadlok VRT, NuBroadlok Edge Sealer, NuBroadlok Moisture Proof Latex Seam Sealer



## Colorways



### Desert Shadows

Color code: 449  
Style number: BC590



### Winter Solstice

Color code: 545  
Style number: BC590



### Natural Linen

Color code: 737  
Style number: BC590



### Potter's Clay

Color code: 739  
Style number: BC590



### Jute

Color code: 747  
Style number: BC590



### Silver Lining

Color code: 939  
Style number: BC590



### Mysterious

Color code: 957  
Style number: BC590



### Twilight

Color code: 575  
Style number: BC590



### Garden Path

Color code: 637  
Style number: BC590

## Testing

Feature	Description
TARR Rating	Heavy
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

## Sustainability

Feature	Description
Embodied Carbon	17.5 kg CO2e/sq m2
Carbon Handprint	-18.375 kg CO2e/sq m2
Beyond Carbon Neutral	-0.875
Total Recycled Content	27%
Pre-Consumer Recycled Content	27%
EPD	Weldlok EPD
HPD	Weldlok HPD
Material Health	Declare Red List Free
NSF 140	<a href="#">Weldlok - NSF 140 Gold</a>
LEED	<a href="#">Calculate LEED on Ecomedes</a>
Indoor Air Quality	GLP 8216
Mindful Materials	Participates
MindClick Rating	Leader
End of Life	ReCover
Country Of Origin	USA

## Warranties

Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static