

# Resistance

## Overview

Feature	Description
Collection	Mass Influence
Style	Resistance (BC428)
Product Type	Broadloom
Size	12Ft 00In
Pattern Repeat	18"W X 19.4"L
Construction	Tufted
Surface Appearance	Textured Patterned loop
Fiber	ColorStrand® Nylon
Dye Method	Solution Dyed / Yarn Dyed
Stain Release Technology	EcoSentry Plus Stain Protection
Soil Release Technology	EcoSentry Soil Protection
Backing	Unibond® Plus
Pile Weight	18.00 oz/yd2 (610 g/m2)
Gauge	1/12 (47.00 rows per 10 cm)
Stitches per Inch	11.17 (43.96 per 10cm)
Pile Thickness	.114" (2.90 mm)
Total Thickness	0.000"
Density	5684
Installation	Glue Down, Double Stick, Tackless
Installation Method	Side Match
Recommended Adhesive	NuBroadlok Premium Plus, NuBroadlok VRT, NuBroadlok Edge Sealer, NuBroadlok Moisture Proof Latex Seam Sealer



## Colorways



### Malabar

Color code: 859  
Style number: BC428



### Cocoon

Color code: 883  
Style number: BC428



### Krypton

Color code: 983  
Style number: BC428



### Distance

Color code: 999  
Style number: BC428

## Testing

Feature	Description
TARR Rating	Heavy
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

## Sustainability

Feature	Description
Embodied Carbon	14.9 kg CO2e/sq m2
Carbon Handprint	-15.645 kg CO2e/sq m2
Beyond Carbon Neutral	-0.745
Total Recycled Content	31%
Pre-Consumer Recycled Content	31%
EPD	Unibond Plus EPD
HPD	Unibond Plus HPD
Material Health	Declare Red List Free
NSF 140	<a href="#">Unibond Plus - NSF 140 Gold</a>
LEED	<a href="#">Calculate LEED on Ecomedes</a>
Indoor Air Quality	GLP 3802
Mindful Materials	Participates
MindClick Rating	Leader
End of Life	ReCover
Country Of Origin	USA

## Warranties

Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static