

Side Stripe

Overview

| Feature | Description |
|--------------------------|--|
| Collection | Learn and Live |
| Style | Side Stripe (GT419) |
| Product Type | Carpet Tile |
| Size | 24" X 24" |
| Construction | Tufted |
| Surface Appearance | Textured Patterned Loop |
| Fiber | Duracolor® Tricor Premium Nylon |
| Dye Method | Solution Dyed |
| Stain Release Technology | Permanent, Built into Fiber |
| Soil Release Technology | EcoSentry Soil Protection |
| Backing | EcoFlex ONE |
| Pile Weight | 17.00 oz/yd2 (576 g/m2) |
| Gauge | 1/12 (47.00 rows per 10 cm) |
| Stitches per Inch | 12.4 (48.82 per 10cm) |
| Total Thickness | 0.224" (5.69 mm) |
| Density | 7650 |
| Installation | Glue Down, FlexLok |
| Installation Method | Brick Ashlar, Monolithic, Multi-Directional, |
| | Quarter Turn, Vertical Ashlar |
| Recommended Adhesive | Enpress, M700 Plus, FlexLok+ Tabs, Total |
| | Bond |



Recommended Installation Methods









Brick Ashlar

Multi-Directional

Quarter Turn

Vertical Ashlar











Mohawk Group

Colorways



City Park

Color code: 562 GT419 Style number:



Fairview

Color code: 853 GT419 Style number:



Franklin

Color code: 859 Style number: GT419



Heritage

Color code: 963 Style number: GT419



Southeast

Color code: 964 Style number: GT419



Westpoint

Color code: 965 Style number: GT419

Colorways



Central

Color code: 566 GT419 Style number:



Eastside

Color code: 961 Style number: GT419

Testing

| Feature | Description |
|-------------------|---------------------------------|
| TARR Rating | Severe |
| GSA Stain Release | Pass |
| Flammability | (ASTM E648) Class 1 - Glue Down |
| Static Propensity | (AATC 134) Under 3.5 KV |
| Smoke Density | (ASTM E662) Less than 450 |

Sustainability

| Feature | Description |
|-------------------------------|---|
| Embodied Carbon | 5.13 kg CO2e/sq m2 |
| Carbon Handprint | -5.39 kg CO2e/sq m2 |
| Beyond Carbon Neutral | -0.26 |
| Total Recycled Content | 74% |
| Pre-Consumer Recycled Content | 59% |
| EPD | EcoFlex ONE EPD |
| HPD | HPD 2.1 EcoFlex ONE Gold - 1000 ppm |
| Material Health | Declare Red List Free |
| NSF 140 | EcoFlex ONE - NSF 140 Gold |
| LEED | Calculate LEED on Ecomedes |
| Indoor Air Quality | GLP 1171 |
| Mindful Materials | Participates in Mindful Materials Library |
| MindClick Rating | Achiever |
| Country Of Origin | USA |



















Packaging

| Feature | Description |
|-------------------------|-------------|
| Square Yards Per Carton | 8.00 |
| Cartons Per Pallet | 22 |
| Weight Per Carton | 43.74 |

Warranties

Lifetime Limited Carpet Tile Warranty, Lifetime Limited Duracolor Stain Warranty, Lifetime Static







