


# Statement Fabric

## Overview

Feature	Description
Collection	Dexterity
Style	Statement Fabric (BT448)
Product Type	Carpet Tile
Size	24" X 24"
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Fiber	EnviroStrand™ PET
Dye Method	Solution Dyed
Soil Release Technology	EcoSentry Soil Protection
Backing	EcoFlex Matrix
Pile Weight	16.00 oz/yd2 (543 g/m2)
Gauge	1/12 (47.00 rows per 10 cm)
Stitches per Inch	11 (43.31 per 10cm)
Pile Thickness	.074" (1.87 mm)
Total Thickness	0.000"
Density	7783
Installation	FlexLok
Installation Method	Quarter Turn, Monolithic, Vertical Ashlar, Brick Ashlar
Recommended Adhesive	Enpress, M700 Plus, FlexLok+ Tabs, Total Bond




## Recommended Installation Methods




Quarter Turn



Monolithic



Vertical Ashlar



Brick Ashlar

## Colorways



### Deep Navy

Color code: 559  
Style number: BT448



### Beige Tone

Color code: 828  
Style number: BT448



### Neutral MIX

Color code: 888  
Style number: BT448



### Light Slate

Color code: 949  
Style number: BT448



### Mid Grey

Color code: 978  
Style number: BT448



### Dark Charcoal

Color code: 989  
Style number: BT448

## Testing

Feature	Description
TARR Rating	Heavy
GSA Stain Release	Pass
Flammability	(ASTM E648) Class 1 - Glue Down
Static Propensity	(AATC 134) Under 3.5 KV
Smoke Density	(ASTM E662) Less than 450

## Sustainability

Feature	Description
Embodied Carbon	7.19 kg CO2e/sq m2
Carbon Handprint	-7.55 kg CO2e/sq m2
Beyond Carbon Neutral	-0.36
Total Recycled Content	45%
Pre-Consumer Recycled Content	45%
EPD	EcoFlex Matrix EPD
HPD	EcoFlex Matrix HPD
Material Health	Declare Red List Free
NSF 140	<a href="#">EcoFlex Matrix - NSF 140 Gold</a>
LEED	<a href="#">Calculate LEED on Ecomedes</a>
Indoor Air Quality	GLP 100055
Mindful Materials	Participates
MindClick Rating	Achiever
End of Life	ReCover
Country Of Origin	USA

## Packaging

Feature	Description
Square Yards Per Carton	10.67
Cartons Per Pallet	22
Weight Per Carton	37.92

## Warranties

10 Year Limited Carpet Tile Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants